

Pull-cord push-button switch 10A 250V~ with fast terminal connection system

REF 75153-39



BASIC INFORMATION

COMPATIBILITY

Simon 75, Simon 82 Detail, Simon 82 Nature, Simon 82 and Simon 88 frames

PACKAGING CONTENTS

Mechanism

TECHNICAL INFORMATION

MARKET AVAILABLE

CE

CABLE SECTION ADMITTED (MM)

From 0,2 to 0,5 mm

IP RATING

IP20

NUMBER OF POSSIBLE ELEMENTS

1 element

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

TYPE OF MECHANISM

Pull cord

VERSION

Single

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

13 mm

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION TYPE

Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION

Screw

REGULATION

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-1:1999 + EN 60669-1:1999 A1:2002 + EN 60669-1:1999 A2:2008

LOGISTICS INFORMATION

PRODUCT VOLUME

3409560 MMQ

PRODUCT NET WEIGHT

0.076 KGM

PRODUCT GROSS WEIGHT

0.076 KGM

PACKAGING QUANTITY

10

PACKAGING HEIGHT

82 MMT

PACKAGING WIDTH

165 MMT

PACKAGING LENGTH

252 MMT

PACKAGING VOLUME

3409560 MMQ

PACKAGING NET WEIGHT

0.76 KGM

PACKAGING GROSS WEIGHT

0.76 KGM

PACKAGING EAN

8421053026229